




RUOTE DENTATE CILINDRICHE

Ruote dentate cilindriche

Angolo di pressione 20°



MATERIALE: C 45 UNI 7845

LARGHEZZA FASCIA "B" PER:

MODULO 1	= 15 mm
MODULO 1.5	= 17 mm
MODULO 2	= 20 mm
MODULO 2.5	= 25 mm
MODULO 3	= 30 mm
MODULO 4	= 40 mm
MODULO 5	= 50 mm
MODULO 6	= 60 mm

Z	MODULO 1				MODULO 1.5				MODULO 2				MODULO 2.5			
	d _e	d _p	d _m	D ₁	d _e	d _p	d _m	D ₁	d _e	d _p	d _m	D ₁	d _e	d _p	d _m	D ₁
55																
57																
60																
65													167.5	162.5		20
70													180.0	175.0		20
72	74	72		12	111.0	108.0		20	148	144		20	185.0	180.0		20
75	77	75		12	115.5	112.5		20	154	150		20	192.5	187.5		20
76	78	76		12	117.0	114.0		20	156	152		20	195.0	190.0		20
80	82	80		12	123.0	120.0		20	164	160		20	205.0	200.0		25
85	87	85		12	130.5	127.5		20	174	170		20	217.5	212.5		25
90	92	90		12	138.0	135.0		20	184	180		20	230.0	225.0		25
95	97	95		12	145.5	142.5		20	194	190		20	242.5	237.5		25
100	102	100		12	153.0	150.0		20	204	200		20	255.0	250.0		25
110	112	110		12	168.0	165.0		20	224	220		20	280.0	275.0		25
114	116	114		12	174.0	171.0		20	232	228		20	290.0	285.0		25
120	122	120		12	183.0	180.0		20	244	240		20	305.0	300.0		25
127	129	127		12	193.5	190.5		20	258	254		20	322.5	317.5		25

Z	MODULO 3				MODULO 4				MODULO 5				MODULO 6			
	d _e	d _p	d _m	D ₁	d _e	d _p	d _m	D ₁	d _e	d _p	d _m	D ₁	d _e	d _p	d _m	D ₁
28													180	168		25
30													192	180		25
32									170	160		25	204	192		25
35									185	175		25	222	210		25
38					160	152		25	200	190		30	240	228		25
40					168	160		25	210	200		30	252	240		25
45					188	180		25	235	225		30				
48					200	192		25	250	240		30				
50	156	150		25	208	200		25	260	250		30				
52	162	156		25	216	208		25	270	260		30				
55	171	165		25	228	220		25	285	275		30				
57	177	171		25	236	228		25	295	285		30				
60	186	180		25	248	240		25	310	300		30				
65	201	195		25	268	260		25	335	325		30				
70	216	210		25	288	280		25	360	350		30				
72	222	216		25												
75	231	225		25	308	300		25	385	375		30				
76	234	228		25	312	304		25	390	380		30				
80	246	240		25	328	320		25	410	400		30				
85	261	255		25	348	340		25	435	425		30				
90	276	270		25	368	360		25	460	450		30				
95	291	285		25	388	380		25	485	475		30				
100	306	300		25	408	400		25	510	500		30				
110	336	330		25	448	440		25	560	550		30				
114	348	342		25	464	456		25	580	570		30				
120	366	360		25												
127	387	381		25												